

## The Numbers Do Not Lie

- EPDM flat roof membranes have a life expectancy of at least 50 years.
- Half-century track record of performance and durability.
- EPDM is Environmentally Friendly.

## Unrivalled

- Unmatched weatherability
- Flexibility
- Economical
- First manufacturer to exceed 10 billion square feet of EPDM membrane production.
- Pressure-sensitive accessories available for virtually any penetration or detail.

## For You

- Wide variety of sheet thicknesses and widths – To suit each individual project and customer needs.
- Seamless – Completely Reliable
- Safe – Heat free installation.

## Adhesives and Sealants

The success of ClassicBond EPDM is not only due to its many exceptional characteristics, including material longevity, weatherability and elasticity but also its accessories

Classic Bond adhesives and sealants are available for all installation requirements. Due to their reliability, speed and ease of installation Classic Bond provides you with the solution to your flat roof problem.

### ClassicBond Deck Adhesive



High strength, low odor, fast curing water based adhesive designed for adhering Classic Bond membranes to all roof deck areas.

Adhesive Properties and Characteristics	
Colour	Liquid - White/Cream Dried - Brown
Base	Acrylic
Packaging	5L and 16 Litres
Shelf Life	1 year

### ClassicBond Bonding Adhesive



A high strength, solvent based contact adhesive. For bonding of membranes to various substrates, upstand details and deck areas. Designed for application with a spreader, brush or medium pile roller.

Adhesive Properties and Characteristics	
Colour	Beige
Base	Neoprene
Packaging	2.5L & 5 Liters
Shelf Life	1 year

### ClassicBond EPDM Primer



A solvent based product designed for one step cleaning and priming of EPDM surfaces prior to the application of all Pressure Sensitive products.

Adhesive Properties and Characteristics	
Colour	Bronze to olive
Base	Synthetic Rubber
Packaging	1L & 3.8 Litres
Shelf Life	6 Months

## The Numbers Do Not Lie

- **EPDM flat roof** membranes have a life expectancy of at least 50 years.
- **Half-century** track record of performance and durability.
- **EPDM is Environmentally Friendly.**

## Unrivalled

- **Unmatched weatherability**
- **Flexibility**
- **Economical**
- **First manufacturer** to exceed 10 billion square feet of EPDM membrane production.
- **Pressure-sensitive accessories** available for virtually any penetration or detail.

## For You

- **Wide variety of sheet thicknesses and widths** – To suit each individual project and customer needs.
- **Seamless – Completely Reliable**
- **Safe** – Heat free installation.

### ClassicBond Water Cut-Off Mastic



A one part, low viscosity, self-wetting butyl blend mastic to be used in terminating membranes with a compression type seal.

Adhesive Properties and Characteristics	
Colour	Dark Grey
Base	Synthetic Rubber
Packaging	0.326 Litres
Shelf Life	1 year, unopened

### ClassicBond Weathered Membrane Cleaner



Used to clean in service EPDM that has been exposed to weather and environmental conditions. It helps to loosen and remove dirt and contaminants from the membrane surface leaving a suitable surface for application of primer and subsequent work.

Adhesive Properties and Characteristics	
Colour	Clear
V.O.C's	755 grams/Litre
Packaging	5 gallon

### ClassicBond Lap Sealant



To be used in conjunction with roofing materials. The cured rubber consistency enables the seal to expand and contract with the environment. Ideal for sealing wall chase details

Adhesive Properties and Characteristics	
Colour	Dark Grey
Base	Synthetic Rubber
Packaging	0.326 Litres
Shelf Life	1 year, unopened