

# TECHNICAL DATA BULLETIN

CLASSICBOND: PIPE FLASHING

**TECHNICAL DATA BULLETIN**

**CLASSIC BOND**

## CLASSIC BOND MOLDED PIPE FLASHING

### GENERAL:

Molded Pipe Flashing is a cured precast base flashing for pipes up to 6" (150 mm) in diameter. Pipe Seals are available in standard and pressure-sensitive options in both small and large sizes.

### TYPICAL PROPERTIES AND CHARACTERISTICS:

	<u>Small</u>	<u>Large</u>
Sizes:	2" to 3" Pipe (13 to 75 mm)	4" to 6" Pipe (100 to 150 mm)
Packaging:	10/Ctn.	10/Ctn.
Weight - Standard	5 Lbs./Ctn. (2.25 Kg)	8 Lbs./Ctn. (3.6 Kg)
- Pressure-Sensitive	7 Lbs./Ctn. (3.2 Kg)	11 Lbs./Ctn. (5.0 Kg)
Material: Molded EPDM		
Color: Black		

### CAUTIONS AND WARNINGS:

1. Remove all lead and other flashing.
2. Pipe Seal must have intact rib at top edge, regardless of pipe diameter.
3. Do not overlap deck flanges.

### INSTALLATION:

See appropriate installation guide for pressure-sensitive products.